

DECLARATION OF PERFORMANCE

N° 001/DoP/2014-01-17

1. Unique identification code of the product-type: EB/SM
2. Type, batch or serial number: EB/SM-4700/300
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
 - For use in construction of roads and other trafficked areas
 - For use in construction of railways
 - For use in earthworks, foundations and retaining structures
 - For use in drainage systems
 - For use in external erosion control systems
 - For use in construction of reservoir and dams
 - For use in construction of canals
 - for use in construction of tunnels and underground structures
 - For use in solid waste disposals
 - For use liquid waste containment projects
 - For use in construction of pavements and asphalt overlays
4. Manufacturer / Manufacturing facility / Manufacturer's contact address:

**Eurobent Sp. z o.o.,
58-100 Świdnica,
ul. Kliczkowska 42**

5. The assessment and verification of constancy of performance of the product:

System 2+

Harmonized technical specification:

EN 13249+A1:2005, EN 13250+A1:2005, EN 13251+A1:2005, EN 13252+A1:2005, EN 13253+A1:2005, EN 13254+A1:2005, EN 13255+A1:2005, EN 13256+A1:2005, EN 13257+A1:2005, EN 13265+A1:2005, EN 15381:2008

Poland 58-100 Świdnica, ul. Kliczkowska 42

 tel/fax +48 74 857 50 81

 www.eurobent.com;  office@eurobent.com

IX Wydział Gospodarczy KRS nr 0000297336

Wysokość kapitału zakładowego 50 000,00 zł

NIP 884-26-51-736; REGON 020678548

Sąd Rejonowy dla Wrocławia-Fabrycznej

we Wrocławiu

6. Institute for Testing and Certification SA, Czech Republic, Notified Body No. 1023 has performed the initial inspection of factory and factory production control system 2+ and performs the continuous surveillance, assessment and evaluation of factory production control system 2+, and issued a certificate of factory production control.

INSTITUTE FOR TESTING AND CERTIFICATION, a.s.

trida Tomase Bati 299,

Louky, 763 02 Zlin

Czech Republic

7. Declared performance:

Essential characteristics	Characteristics	Harmonized technical specification
Tensile strength	MD 12,5 kN/m (-10%) CMD 12,5 kN/m (-10%)	EN ISO 10319
Elongation at break	MD 20 % (-10%) CMD 20 % (-10%)	EN ISO 10319
Resistance to static puncture	3,5 kN (-10%)	EN ISO 12236
Dynamic perforation resistance	1 mm	EN ISO 13433
Characteristic opening size (O ₉₀)	95 µm (±20 µm)	EN ISO 12956
Water permeability	32 l/sm ² (-10%) 3,2 * 10 ⁻² m/s (-10%)	EN ISO 11058
Durability	To be declared in accordance with the relevant clause of EN 13253:2014, Annex B.	EN 13253:2014, Annex B

Poland 58-100 Świdnica, ul. Kliczkowska 42

tel/fax +48 74 857 50 81

www.eurobent.com; office@eurobent.com

IX Wydział Gospodarczy KRS nr 0000297336

Wysokość kapitału zakładowego 50 000,00 zł

NIP 884-26-51-736; REGON 020678548

Sąd Rejonowy dla Wrocławia-Fabrycznej

we Wrocławiu

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

.....

(name, surname, function)

Świdnica, 17.01.2014
(place and date of issue)

.....
(signature)